

**TESTING AND MEASURING EQUIPMENT/ALLOWED SUBCONTRACTING**  
**IEC 60730-2-8:2000/AMD1:2002/AMD2:2015, Edition 2.0**  
**Automatic electrical controls for household and similar use – Part 2-8: Particular requirements for electrically operated water valves, including mechanical requirements**

“R”	Required
“S”	May be subcontracted, see OD 2012
“SPTL”	Specialized Facility, see IECEE 02-2
“W”	Witness testing in the categories “MED” and “MEAS”
“3PPS”	Three Phase Power Supply required

Clause	Measurement/testing	Testing / measuring equipment / material needed	Subcontracting
3	General requirements	None	-
4	General notes on tests	None	-
5	Rating	None	-
6	Classification	None	-
7	Information	None	-
8	Protection against electric shock	Test finger (Fig. 2 of IEC 60730-1), force gauge, test pin (Fig. 1 of IEC 60730-1), milliampmeter, voltmeter, ruler, micrometer	R
9	Provision of protective earthing	Ammeter, voltmeter, vernier calipers	R
		Appropriate material analyzing equipment (e.g. scanning electron microscope, energy dispersive x-ray spectrometer)	S
10	Terminals and terminations	According to IEC 60998, Torque tester, force/pull gauge tester, screwdriver, micrometer, ruler, flexing tester	R

Clause	Measurement/testing	Testing / measuring equipment / material needed	Subcontracting
11	Construction requirements	Electric strength tester, HV test supply, isolation transformer, insulation tester, DC voltage supply, flexing tester, voltmeter, ammeter, freezer chamber, temperature recorder, torque tester, force gauge, time clock, test fingernail, vernier callipers or suitable measuring instrument, micrometer, pressure gauge	R
12	Moisture and dust resistance	According to IEC 60529, electric strength tester, conditioning chambers: heat-humidity, leakage current meter, metal foil	R
13	Electric strength and insulation resistance	Insulation tester, electric strength tester with a trip current $\geq 100$ mA, leakage current tester	R
14	Heating	Temperature meter/recorder, fine wire thermocouples, winding resistance measurement system – 4-wire low-ohm meter (if required), environmental chambers (heat, freeze), current loads per ratings, voltmeter, ammeter, regulated power supply, timer, blackened discs of copper or brass, clutch, valve fittings and pipes	R
15	Manufacturing deviation and drift	Voltmeter, ammeter Equipment as required by the type of control such as e.g.pressure meter/recorder, water flow meter, etc. Remark: For those types of controls for which the atmospheric pressure is relevant for the determination of the manufacturer deviation and drift the atmospheric pressure has to be measured by a pressure meter or alternatively it is acceptable to get the information about the atmospheric pressure online via local metrological service.	R
16	Environmental stress	Environmental chambers – heat, freeze, humidity	R
17	Endurance	Environmental chambers – heat, freeze, humidity; pressure meter, voltmeter, ammeter, power analyzer meter, oscilloscope, inductive loads, resistive loads, pilot duty loads, motor loads, activation source and cycling mechanism as required in Annex -BB- or -EE-	R
18	Mechanical strength	Apparatus in IEC 60068-2-75, impact tester (Fig. 4 of IEC 60730-1), tumbling barrel (Fig. 5 of IEC 60730-1), force tester, torque tester, pull tester Additional requirements according to Annexes: -BB-, -CC-, -DD- and -EE-	R  S
19	Threaded parts and connections	Screwdrivers, torque tester	R

Clause	Measurement/testing	Testing / measuring equipment / material needed	Subcontracting
20	Creepage distances, clearances and distances through solid insulation	Measuring ruler, force tester, test finger (Fig. 2 of IEC 60730-1), impulse voltage tester, electric voltage tester, insulation resistance meter, oscilloscope, electric strength tester, micrometer, vernier callipers	R
21	Resistance to heat, fire and tracking	Ball pressure test apparatus in accordance with Fig. 6 of IEC 60730-1, horizontal burning test apparatus (Annex G of IEC 60730-1) and needle flame apparatus, glow-wire test apparatus, environmental chamber or heating cabinet, tracking test apparatus, voltmeter, ammeter	R
22	Resistance to corrosion	Humidity chamber, heating cabinet	R
23	EMC requirements – emission	Apparatus in accordance with CISPR14-1. Equipment in accordance with Clause 17 of IEC 60730-1, oscilloscope	S
24	Components	Test apparatus in accordance with IEC 61558-2-6 (linear xfms) or IEC 61558-2-16 (SMPS), and other IEC component standards voltmeter, ammeter, cotton, non-renewable fuse, power supply with a min. of 1000 A short-circuit supply, timer, electronic test loads, variable resistors, oscilloscope/wattmeter	R
25	Normal operation	Refer to Annex H of IEC 60730-1	-
26	EMC requirements – immunity	Refer to Annex H of IEC 60730-1	-
27	Abnormal operation	Voltmeter, ammeter, electric strength tester, power supply, thermocouples, load banks, timer	R
28	Guide of the use of electronic disconnection	Refer to Annex H of IEC 60730-1	-
Annex A	Indelibility of Marking	Refer to IEC 60730-1	R
Annex B	Measurement Guide	None	-
Annex C	Cotton for Mercury Switch Test	Common as described in Annex C of IEC 60730-1	R
Annex D	Heat, fire and tracking	Informative guide – None	-
Annex E	Circuit for measurement leakage current	Circuit apparatus according to Figure E.1 of IEC 60730-1	R
Annex F	Fire Hazard Testing	Informative guide for IEC 60335 applications – None	-
Annex G	Heat-Fire Resistance Tests	Glow-wire test apparatus per IEC 60695-2-10 and IEC 60695-2-11, Ball pressure test apparatus per IEC 60695-10-2, Fig. 6, PTI Test apparatus per IEC 60112	R

Clause	Measurement/testing	Testing / measuring equipment / material needed	Subcontracting
Annex H	Requirements for Electronic Controls	Refer to Annex H, sub-clauses below:	-
H8	Protection against electric shock	Leakage current meter, capacitance measuring instrument	R
H11	Constructional requirements	Ammeter, voltmeter, chart recorder Remark: For safety software assessments, special emulator tools and set-ups would be required. Agreement between the manufacturer and the CBTL should be established. Details to be recorded in report.	R
H13	Electric strength and insulation resistance	Same as Clause 13 above	R
H17	Endurance	Thermal cycling test apparatus	R
H18	Mechanical Strength	Refer to Clause 18 above	R
H20	Creepage distance, clearance and distance through insulation	Refer to Clause 20 above	R
H23	EMC requirements – emission	Refer to Clause 23 above; equipment in accordance with CISPR 11	S
H25	Normal Operation	Oscilloscope, ammeter, voltmeter	R
H26	EMC requirements – immunity	Environmental chamber, voltage dips and short voltage interruption apparatus, variable voltage supply, 3-phase auto-transformer, surge test apparatus, fast transient/burst test apparatus, ring wave surge test apparatus, conducted radiofrequency test apparatus, radiated EM field test apparatus, programmable logic controllers or similar equipment	S
H27	Abnormal Operation	Voltmeter, ammeter, oscilloscope, temperature meter	R
H28	Guide on use of electronic disconnection	None	-
Annex J	Requirements for thermistor elements and controls using thermistors	Same which are used for Clauses 8 through 28, test apparatus to do R/T measurements	R
Annex K	Nominal voltages	Informative Annex – None	-
Annex L	Overvoltage categories	None	-
Annex M	Typical usage	Informative Annex – None	-
Annex N	Pollution degree	None	-
Annex P	Printed circuit board coating performance test	Heating chamber, humidity chamber, environmental cycling chamber, electric strength tester	R

<b>Clause</b>	<b>Measurement/testing</b>	<b>Testing / measuring equipment / material needed</b>	<b>Subcontracting</b>
Annex Q	Printed circuit board coating performance test	Freezing chamber, environmental cycling chamber, electric strength tester	R
Annex R	Explanatory notes for surge immunity test	Informative Annex – None	-
Annex S	Guidance for applying Clause 20	Informative Annex – None	-
Annex T	Requirements for SELV and PELV	None	-
Annex U	Requirements for relays when used as controls in IEC 60335 appliances	Same which are used for Clauses 7 through 28	R 3PPS
Annex V	Requirements for controls powered by secondary batteries (rechargeable)	Same which are used for Clauses 8 through 28	R
Annex AA	Relation between different flow coefficients	Informative Annex – None	-
Annex BB	Arrangement for measurement of transient pressure caused by water valves	Test bench as described in the arrangements	R
Annex CC	Test on valve bodies of thermoplastic material intended to be connected to the water supply mains	Temperature meter/recorder, fine wire thermocouples, pressure measurement system, environmental heating chamber, voltmeter	S
Annex DD	Torque test for valves with internally threaded end-connections to ISO 7-1	Force tester, torque tester	R
Annex EE	Arrangement for measurement of transient pressure caused by water valves with a declared pressure of up to and including 1,0 MPa (10 bar)	Test bench as described in the arrangements	R